

# Flanged Duct Pipe

## 3201-XX16 - 16ga Galvanized or Stainless Steel

### TECHNICAL DATA

| Ø Size<br>In. | Length<br>In. | Galvanized Steel<br>Std Weight<br>Lbs |
|---------------|---------------|---------------------------------------|
| 26            | 59.00         | 113                                   |
| 28            |               | 123                                   |
| 30            |               | 133                                   |
| 32            |               | 140                                   |
| 34            |               | 152                                   |
| 36            |               | 160                                   |
| 38            |               | 170                                   |
| 40            |               | 180                                   |

| Temperature Rating of<br>Product Components |                        |                  |
|---|------------------------|------------------|
| ° F   | Flanged Pipe, 16 gauge |                  |
| 1100°                                       | Galvanized Steel       | Optional - 304SS |
| 390°  |                        |                  |
| 0°  |                        |                  |
| -60°  |                        |                  |

| Additional Notes   |  |
|--|--|
| <ul style="list-style-type: none"> <li>At temperatures ranging between 390° F and 480° F, the zinc-iron alloy layers in galvanized steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is 390° F.</li> <li>Weights are approximate.</li> </ul> |  |

| Compliance / Rating of<br>Product Components |            |                                 |
|--|------------|---------------------------------|
| Product                                      | Material   | Compliance /<br>Rating          |
| 16ga<br>Flanged<br>Pipe                      | Galvanized | ASTM A527 with a<br>G-90 rating |
|  | SS304      | Finish meets<br>ASTM A240       |

**Construction**  
**Seam:** longitudinal seam is plasma welded.  
**Flanges:** Industry standard Angle Flange retained via 1/2" vanstone lip. Flange fully welded upon request.

